9USB/9USB TALL



Classe 9USB has an eye-catching, futuristic design and is made from tough materials, such as stainless steel and aluminium, so it's packed with character.

Shock-absorbing side panels guarantee a sturdy machine that's practical to use.

Available with 2, 3 and 4 groups and also in a TALL version.



Classe 9USB features advanced electronics and an alphanumeric display for managing the machine's main settings.



Stunning lights on the steel side panels and the floating front panel accentuate the design, lending the machine a strikingly elegant yet bold and trendy look.



Innovative functional elements like the soft-touch button control and ergonomic lighting assist the barista in every phase of use and cleaning.



Classe 9USB has an ergonomic lighting system in the work area to make the barista's job easier plus chrome group covers and all the distinctive stylish accessories from the Rancilio range.



The hot-water temperature control system for tea and infusions has two different temperatures and programmable dosing.







Classe 9USB - 3 groups - front view



Classe 9USB TALL - 3 groups - front view



Classe 9USB - 3 groups - rear view



Classe 9USB - 2 groups - side view























Technical Features independent heat exchangers

idependent neat exchangers	
lectric heating	
uilt-in volumetric pump	
ump pressure gauge	
oiler pressure gauge	
lectronic water level control	
lectronic boiler pressure control	
nultifunctional onboard computer with display and USB port	
ow-voltage brew heads (24 V)	
ow-voltage dispensing controls (24 V)	
ersion "TALL" - H max cups/glasses: 5.7 in (14.5 cm)	
ED lights illuminate the work area, functional LED lights on the group button panels,	

Standard features, accessories

 $\textbf{STANDARD FEATURES:} \ 1 \ \text{filter holder for 2 cups per group, 1 filter holder for 1 cup,}$ 2 steam wands, 1 mixed hot water dispenser with two buttons for programmable timecontrolled dosing and/or temperature (4-TEA), coffee tamper, measuring scoop and $\,$ cleaning discs, levelling feet

ACCESSORIES: DP automatic or manual water softener, MD dosing grinder

Materials

stylish lateral lighting

aluminium and stainless steel body

Technical Data

2 GROUPS

dimensions (w×D×H) 29.5×21.3×20.6 in (750×540×523 mm)		weight 145.5 lb (66 kg)	boiler 11 I (2.4 gal _{uk})
boiler power	voltage	voltage	
4,300 W	220-240 V / 38	220-240 V / 380-415 V (3N)	
3 GROUPS			
dimensions (w _{*D*H})		weight	boiler
39.0×21.3×20.6 in (990×540×523 mm)		174.2 lb (79 kg)	16 l (3.5 gal _{uk})
boiler power	voltage	voltage	
6,000 W	220-240 V / 38	220-240 V / 380-415 V (3N)	

4 GROUPS

dimensions (w-р-н)		weight	boiler
48.3×21.3×20.6 in (1230×540×523 mm)		211.6 lb (96 kg)	22 I (4.8 gal _{uk})
boiler power	voltage		frequency
6,000 W	220-240 V / 380-415 V (3N)		50/60 Hz

Sta	ndard			
	C-LEVER	4-TEA Temperature programming	ABM.07 Smart power management	V-FLEX Voltage stabilizer
_	EASY FIX ed diagnostics	PLUG & BREW	LEASY CLEAN Automatic washing program	HYDRO HUB Ergonomic hydraulic module
	LED LIGHTS	SOFT TOUCH	ERGO-FILTER HOLDER Ergonomic filter holder	GRID SYSTEM



On demand







